


Self-Ordering Kiosk 21,5



FHD



2GB+32GB



10 touch points



Android 11
Optional



Multilanguage
support



QR CODE



Windows



WIFI

Display	
Size(optional)	21.5inch
Model	TP-215
Screen	21.5" TFT LED
Display area / Proportion	477(W)*268(H) mm 16:9
Physical resolution	1920x1080(pixels)
Display color	16.7M(8-bit)
Contrast(typ)	1500:1
Brightness	250cd/m ²
Viewing angle	(up/under/left/right):89° /89° /89° /89°
Response time	6ms
Printer	
Printer specifications	80mm
Printing method	Thermal dot printing
Resolution ratio	8dots/mm
Effective printing width	72mm
BAUD	9600bps-11520bps
Cutting knife	Support full cut or half cut
QR code scanner (Optional)	
Sensor	640(H) X 480(V)CMOS
Light source	White light fill/coloured light alert
Identification code system	Code39, Code93, CodaBar, Interleaved 2 of 5, Industrial 25, Matrix 2 of 5, Code11, MSI, RSS-14 Qualified RSS, Extended RSS
Identify angles	Rotation 360° , Tilt ± 60° , Deflection ± 60°
Recognition accuracy	1D code ≥5mil QR code ≥10mil
Read depth of field	EAN -132~11.0cm (13mil) /Code1282.5 ~ 13.0cm (15mil)
Card reader(Optional)	
Serial Port Configuration	Baud: 115200 (default); Data bits: 8; Start bit: 1; Stop bit: 1; Check bit: NONE
Operating Frequency	13.56MHz
Support cards	Contactless card: Mifare One S50/S70、Mifare UltraLight NTAG213/215/216

Computer configuration

CPU	Standard: INTEL Core i5/8th Gen
RAM	4G
HDD	128G
Ports	RJ45×1(GIGA LAN 10\100\1000M)、USB×3
OS	WINDOWS 10 Pro

Windows System

Network	LAN, WIFI
Voice	Built-in mini dual speakers

Other

Reliability	50000h
Working Temperature	0℃~ 50℃
Humidity	-20℃~ 60℃
Working humidity	5%~90%
Store humidity	5%~90%
Quality standard	(3C)/Compulsory certification of Chinese electrical products (3C)
Environmental standards	All components and packaging materials comply with international environmental standards.

Power supply

Supply voltage	90V-240V/50HZ-60HZ
----------------	--------------------

Size

Screen size(mm)	477*268
Main Unit Packaging Dimensions(mm)	970*600*680
Stand Packaging Dimensions(mm)	1080*430*220

Product display

